



8 Channels 3G HD-SDI Broadcast Video With 8 Channels Bi-Directional Data Over One Fiber

DL815

DL Series

Email: sales@vi-link.net - Tel: 714-312-0654 - Web: www.vi-link.net

Overview

Vi-Link HD SDI Video equipment: The DL815 is a fiber optic digital multiplexer that designed to transmit up to 8 channels of high quality uncompressed digital 3G HD SDI video signals and Bi-directional EIA-RS232 or RS-422 Data over one single mode cable. It is a cost effective selection for transporting high quality SDI camera pictures and Ethernet network link from the remote location to the operation center via long fiber optic cable.

The DL815 is compatible with all SMPTE rates: *SMPTE259M SDI from 143 to 360 Mbps, SMPTE344M 540Mbps, SMPTE292M HD-SDI 1.485 Gbps, SMPTE372M Dual Link HD-SDI 2,97 Gbps, SMPTE424M Dual Speed 3G-SDI 2.97 Gbps.*

The DL815 offers a fully serial digital video encoding/decoding of real time high quality digital video providing adjustment free operation over a wide operational range. Using automatic gain control and state-of-the-art multiplexing, combining with CWDM technologies for distances from back-to-back to 50 Kilometers, our digital signaling offers superior receiver output stability, which is unaffected by changes in fiber path attenuation due to aging or splicing points.

The extended temperature capability of the DL815 satisfies very critical applications requiring high quality video performance with high reliability.

Applications include Broadcast Video Production, Video Editing, Unmanned Aircraft Vehicle Days & Nights Monitoring Systems, ITS Intelligent Traffic System, Metro & Railroad Monitoring System, Homeland Security, Utility Management, Premise Networks, Military Hardened applications or anything requiring HD quality video performance.



Features

- 8 Channels Digital Broadcast Video Transmission
- 8 Channels Bi-Directional Data
- Single Mode Fiber With CWDM Technology
- Real Time High Quality 3G-HD-SDI Video
- Compatible with all SMPTE3G SDI Rates
 - SMPTE259M SDI from 143 to 360 Mbps, SMPTE344M 540Mbps,
 - SMPTE292M HD-SDI 1.485 Gbps, SMPTE372M Dual Link HD-SDI 2,97 Gbps,
 - SMPTE424M Dual Speed 3G-SDI 2.97 Gbps
- Fully Compliant with EIA RS-232/RS-422 standard
- Asynchronous Data Speed Up to 115 Kbps
- 90~240 VAC or +24 VDC, +28 VDC, -48 VDC
- NEMA Temperature

Applications

- Broadcasting Video Transmission
- High Quality HD-SDI Video Monitoring in Traffic Control System
- METRO Security System
- Unmanned Aircraft Video System
- Oil & Gas Perimeter Intruder Detection
- Military Applications
- Premise Networks
- Any High Quality Video Requirement

Order Information

Model	Descriptions
DL815T23ST05	8 Channels 3G HD SDI Video (Tx) and Bi-Directional Data Over Fiber, CWDM, SM ST, 50Km, 90~240 VAC
DL815R23ST05	8 Channels 3G HD SDI Video (Rx) and Bi-Directional Data Over Fiber, CWDM, SM ST, 50Km, 90~240 VAC


*** Replace 23 with 22 For RS-422 Interfaces***

Specifications

System:	
Error Rate	1 in 10 ¹² or Better
Indicators	Pwr, Video, Data
Optical:	
Transmitter	CWDM Lasers
Tx	1430nm~1610nm
Rx	1450nm
Receiver	PIN
Tx	1450nm
Rx	1430nm~1610nm
Power Budget	20 dB @ SM
Connector	ST
Environment:	
Operating	-34 ^o C to +74 ^o C
Storage	-40 ^o C to + 95 ^o C
Humidity	98% Non-Condensing
Physical:	
Dimensions	19" x 10" x 1.75"
Weight	7 lbs

3G HD-SDI Video Interface:	
Channel	8 x 3G HD-SDI
Format	SMPTE 259M, 292M and 424M
Speed	143M~540M, 1.485GB~2.97 GB
Full HD Revolution	1280 x 720P @ 50/60fps 1920 x 1080P @ 50/60fps
Signal Level	800mVp-p +/-10%
Connector	BNC
Impedance	75 Ohms
Bi-Directional Data:	
Channel	8
Data Type	Asynchronous
Speed	DC to 115 Kbps
Format	EIA-RS-232 / EIA-RS-422
Connector	RJ45
Power:	
AC	90~240 VAC @ 0.5Amp 50/60Hz
DC	+24 VDC, +28VDC, -48 VDC

Application



All statements, technical information and recommendations related to the products herein are based upon information believed to be reliable or accurate at the time of publication. However, the accuracy or completeness of the information given is not guaranteed and no responsibility is assumed for any inaccuracies. Please contact Vi-Link, Inc. for more information. Vi-Link, Inc. and Vi-Link Logo are trademarks of Vi-Link, Inc.