



# 8 Channels HD Analog Video AHD-CVI-TVI (1~5MPX) PTZ Data Over One Fiber

# HL8D

Email: sales@vi-link.net - Tel: 714-312-0654 - Web: www.vi-link.net

## HL Series

## Overview

**Vi-Link High Definition Analog Video equipment:** The HL8D is a fiber optic digital transmitter/multiplexer for transmitting 8 channels of Analog HD 5MPX, 4MPX, 3MPX, 2MPX, 1MPX, TVI/CVI/AHD video signals with PTZ data over a single mode fiber optic cable. This robust transmission platform utilizes the existing Coaxial and Fiber Optic cables in the existing system, it is a very cost effective solution for upgrading the old CCTV Analog Video System to the today HDcctv High Definition Analog Video System.

The HL8D is fully recognized all high definition analog video input formats including 25/30/50/60 fps @720P and 25/30 fps @ 1080P, its BNC interface can support up to 500m @ 720P and 300m @1080P. The Multiplexer/De-Multiplexer also offers a fully serial digital video encoding/decoding of real time TVI/CVI/AHD video (10 bits sampling rate at 108 Mhz) providing adjustment free operation over a wide operational range. Utilizing fiber optic AGC receiver techniques for distances from back-to-back to 50 Km, our digital signaling offers superior receiver output stability, which is unaffected by changes in fiber path attenuation due to aging or splicing points. The extended temperature capability of the HL8D satisfies very critical applications requiring high quality video performance with high reliability.

In addition, the HL8D provides Auto Signal Compensation (ASC) allowing low signal distortion compensation over long distance transmission. The transmitter is a rugged standalone compact unit and the receiver is also a rugged standalone or a plug-in card for the rack version.

Applications include City and Highway Traffic Monitoring, METRO and Railroad Monitoring, Oil & Gas Monitoring, campus Security Monitoring, Airport Security System, Military Security Systems or any application requiring HD quality video performance.



## Features

- 8 Channels HD Analog (TVI/CVI/AHD) Video
- PTZ Camera Control Data
- Real Time Digital Video Transmission
- Up to 5 MPX @ 1080P, 2560 x 1920P
- Sampling Rate 108 Mhz @ 10 Bits
- Supports 25/30/50/60 fps @ 720P and 25/30 fps @ 1080P, 1520p, 1960p
- Coax Cable supports 300m @ 1080P
- RS-485 PTZ Control Data Interface up to 9.6 Kbps
- AGC Single mode Transmission of 0 to 40 Km
- Standalone & Plug-in Rack Card
- NEMA Temperature

## Applications

- City and Highway Monitoring
- Metro and Railroad Monitoring
- Oil & Gas Pipeline Monitoring
- Airport Security Systems
- Utility Systems
- Military Applications
- Premise Networks
- Any Digital HD Video Monitoring Requirement

## Order Information

Model	Descriptions
HL8DTST03	8-ch HD Analog 5PMX TVI/CVI/AHD (Video Tx), Uni-Directional RS-485 Data, 1550/1310nm SM ST, 40Km, +5 VDC
HL8DRST03	8-ch HD Analog 5MPX TVI/CVI/AHD (Video Rx), Uni-Directional RS-485 Data, 1310/1550nm SM ST, 40Km, +5 VDC

\*\*\* add -422 for RS-422 Interfaces\*\*\*

### Specifications

<b>System:</b>	
Error Rate	1 in 10 <sup>12</sup> or Better
Indicators	PWR, Video Active, Data
<b>Optical:</b>	
Transmitter	Lasers
Tx	1490nm & 1550nm @ 3Gbps
Rx	1310nm
Receiver	PIN
Tx	1310nm @ 125 Mbps
Rx	1490nm & 1550nm
Power Budget	20 dB @ SM
Connector	ST
<b>Environment:</b>	
Operating	-34 <sup>o</sup> C to +74 <sup>o</sup> C
Storage	-40 <sup>o</sup> C to + 95 <sup>o</sup> C
Humidity	98% Non-Condensing
<b>Power:</b>	
Standalone	+5 VDC
Rack Chassis	90~240 VAC

<b>TVI/CVI/AHD Video Interface:</b>	
Channel	8
Video Bandwidth	Up to 5 MPX
Full HD Revolution	720P @ 25/30/50/60fps 1080P, 1520P, 1960P @ 25/30fps
Sampling Frequency	108 MHz @ 10 bits
Signal Level	1Vp-p +/-10%
Connector	BNC
Impedance	75 Ohms
Coaxial Distance	300m@1080P
Indicator	TX/RX
<b>PTZ Data:</b>	
Channel	1 (Uni-Directional)
Format	IEA RS-485
Speed	DC to 9.6 Kbps
Connector	Terminal Block
<b>Physical:</b>	
Dimensions	
Standalone	1" x 5" x 4"
Rack	19" x 12" x 4"

### Application

