



**Vi-Link**

*Fiber Optic Communications*

# Fiber Optic Media Converter 10/100M SC

# MC100

Email: sales@vi-link.net - Tel: 714-312-0654 - Web: www.vi-link.net

## MC Series

## Overview

The MC100 Web Management Media Converter series is designed to operate in high temperature NEMA environment with 1 x 10/100Mbps copper port and 1 x 100Base Fiber Optic Fast Ethernet Port. The converter mediates between a 10/100M Base-TX segment and a 100Base-FX segment. It is primarily designed for large, higher speed/bandwidth demanding workgroups that require expansion of the Ethernet network. It can extend the conventional 10M Ethernet or 100M Fast Ethernet to 20Km~100Km via the Gigabit Ethernet Fiber-optical Line. It is high-performance, cost effective and flexible solutions for a wide range of applications in the field of LAN campus network.

With its built-in Web-based management, the MC100 offers an easy-to-use and configuration facility, via the WEB interface, it can be programmed for basic management functions such as per port speed duplex settings, Port Trunking, VLAN, Port Mirroring, network security authentication and misc configurations. Additionally, the firmware includes advanced features such as IGMP snooping, QoS (Quality of Service), broadcast storm and bandwidth control, to enhance bandwidth utilization. The extended temperature capability for meeting NEMA specifications satisfies very critical applications requiring high quality data transmission performance with high reliability. Applications include ITS Intelligent Traffic System, Metro Operation, HDTV Broadcasting System, IP cameras Surveillance, Homeland Security, Utility Management, Premise Networks, Military Hardened applications or anything requiring high speed Ethernet Network performance.



## Features

- 1 x 100M FX Fiber Port
- 1 x 10/100M TX Ethernet Ports
- Support 802.1Q 4K VLAN, port based, protocol based VLAN, Generic Attribute Registration Protocol (GARP), GARP VLAN Registration Protocol (GVRP)
- Static and Dynamic port aggregation
- Port rate limit, broadcast storm control, port mirroring, rich Quality of Service (QoS) features
- +5 VDC Power Adapter

## Applications

- ITS Traffic Applications
- SCADA Networks
- Metro Networks
- Gas & Oil Fields Monitoring Applications
- Railroad Networks
- Military Applications
- Data Acquisition Applications

## Order Information

Model	Descriptions
MC100SC03	Ethernet Media Converter, 1 x 100M-FX SC, SM 1310nm, 50 Km, 1 x 10/100M-TX RJ45 , +5 VDC

## Specifications

### System:

Error Rate	1 in 10 <sup>12</sup> or Better
Network Standard	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3z FX IEEE 802.3x Flow Control IEEE 802.3ad Port trunk with LACP IEEE 802.3w RSTP IEEE 802.1Q VLAN Tagging
Indicators	PWR, TP, FO, 100M
Ports	1 x 10/100Base-T 1x 100Base- FX
Frame Flow Control	Full Duplex Mode
Frame size	16K Bytes
Jumbo Frame	9000 Bytes
Layer 2 Management	Store-and Forward Remote Monitoring (RMON) Far-end Fault Indication (FEFI) Link Fault Pass Through (LFP) Auto Recovery Remote Management and Set Up Manual IP Address Setting / DHCP Loopback, Broadcast, Multicast, Unicast storm control Speed Duplex Mode Configuration Bandwidth Control on TP/FX

### Physical:

Dimension	6.5" x 5.5" x 1.5"
Power	+24 VDC @1 Amp

### Fiber Interface:

Port	1 x 100Base-FX
Data Rate	100 Mbps
Connector	SC
Distances	2KM@850MM, 10KM@1310MM 40KM@1310SM, 100KM@1550SM

### TX Interface:

TX Port	1 x 10/100Base-TX Auto-Negotiation MDI/MDIX
Data Rate	10/100 Mbps
Connector	RJ45
Transmission Mode	Half/Full Duplex

### Network Management :


Interface	Web Browser, SNMPv1, v2c Monitor
Port Configuration	Port enable, Auto-Negotiation, Full and Half Duplex mode, Flow Control Enable, Bandwidth Control
VLAN	16 IEEE 802.1Q VLAN / Q-in-Q VLAN
Link Aggregation	Supports IEEE 802.3ad LACP
QoS	802.1p Priority, DSCP field in IP
IGMP Snooping	IGMP (v1/v2) Snooping, up to 64 Multicast groups
SNMP MIBs	RFC-1213 MIB-2, RFC-1573 MIB RFC-2819 RMON MIB (Group 1)

### Environment:

Operating	-34 <sup>o</sup> C to +74 <sup>o</sup> C
Storage	-40 <sup>o</sup> C to + 95 <sup>o</sup> C
Humidity	98% Non-Condensing


## Application

### 10/100M TX Ethernet RJ45 At Remote Location



MC100

Up to 50 Km SM Fibers



MC100

### Operation Center



### 10/100M TX Ethernet RJ45

All statements, technical information and recommendations related to the products herein are based upon information believed to be reliable or accurate at the time of publication. However, the accuracy or completeness of the information given is not guaranteed and no responsibility is assumed for any inaccuracies. Please contact Vi-Link, Inc. for more information. Vi-Link, Inc. and Vi-Link Logo are trademarks of Vi-Link, Inc.