VILINK Communications Inc.

Full HD 3M 1080P IP POE Dome Camera

HDccTV Equipment

Model CE540

Features

- *Up to 3 Megapixel Resolution*
- *HD Real time Video*
- *DWDR & 3D DNR*
- *True Day & Night with IR CUT*
- *H.264 High Profile Algorithm*
- *Main Stream and Sub Stream Encoding*
- *Support ONVIF Protocol*
- *Support Mobile Monitoring*

Main Parameters:

Camera:	
Image Device	1/3" Progressive CMOS
Shutter Time	1/25S ~ 1/1000S
Len	2.8 ~ 12 mm Vari focal Lens
Len Mount	^{0}14
Day & Night	ICR
WDR	Digital WDR
DNR	3D DNR
Minimum Illumination	Color: 0.01 LUX @ F1.2
	B&W: 0 LUX (With IR)
Video:	
Video Compression	H.264
H.264 Profile	High Profile
Resolution	2048*1536, 704*576, 352*288
Bit Rate	Main Stream: 01Mbps ~8Mbps
	Sub Stream: 32Kbps ~ 512Kbps
Frame Rate	50/60Hz: 16fps (2048 x 1536)

Network:	
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, FTP, UPNP
Alarm Trigger	Motion Detection, Video Analysis
Remote Access	UC, IE, Mobil Phone
Support	Onvif Protocol
Interface	10/100M Ethernet Port
Interface Connector	RJ45
Environment:	
Operating	-10^{0} C to +65^{0}C
Storage	-30^{0}C to + 85^{0}C
Humidity	98% Non-Condensing
Water Proof Case	IP66
Power:	
Adapter	+12 VDC or POE
Physical:	
Dimensions	3.5" x 3.5" 3.5"
Weight	2 lbs

450 Goddard, Irvine, California 92618 – Tel: 714-312-0411 – Fax: 949-789-8890
Email: sales@vilinknet.com – Web: www.vilinknet.com